



MS652+

Wearable 2D Ring Scanner

After the success of MS652 wearable 2D ring scanner in the global market, unitech electronics recently announced upgrade to MS652+ wearable 2D ring scanner. Delivering great customer experience to our users, the MS652+ barcode scanner has been upgraded the Bluetooth module that it supports both Bluetooth® classic V2.1 classic + EDR, Class 1 and Bluetooth® Low Energy 4.2. It enables improved data transmission rates and efficient power consumption (Bluetooth® Low Energy 4.2), as well as the Bluetooth® classic V2.1 SPP protocol allows the duplex communication for devices. Also the SPP protocol enhanced the pairing experience for devices. The MS652+, featuring wearable design that gives users freedom of movement to perform barcode scanning tasks comfortably while keeping both hands free. The MS652+ is designed to streamline the workflow for a wide range of applications such as retail, logistics, field service and hospitality.

Ergonomic design for mobile operators

The MS652+ wearable 2D ring scanner enables its operator to move products, packages, materials and proceed with their barcode reading tasks more efficiently, safely and comfortably. Whether you prefer left or right-handed operation, users can instantly switch between right and left hand operation with the special one push rotate design. It improves productivity in your operations with the wearable technology.

Small but Durable

The MS652+ is small but extremely rugged which supports IP42 protection against water and dust as long as 1.5 meters drop-resistant housing. In addition, the MS652+ is built in changeable and rechargeable battery pack that allows users to improve your work productivity at work. With an ergonomic and compact design, the MS652+ 2D ring scanner delivers users powerful way to improve efficiency to the next level.

Features

- Lightweight and unique wearable ring design
- One push rotate design allows right and left hand operation switch easily.
- Available to read 1D, 2D and PDF417 barcodes
- Flexibility wireless design with 100M operation range
- Rugged and durable design with IP42 and 1.5m drops
- Bluetooth® Low Energy 4.2 / classic V2.1 classic + EDR, Class 1 and NFC technology: Easily pair to smart phones and tablets (iOS/ Android devices)
- Changeable and rechargeable battery pack
- Full Shift Battery Life: Up to 13 Hours
- Mounted on two fingers to enhance the operation stability

Ultimate 2D wireless ring scanner

Featuring a superior scan engine, MS652+ is available to scan most 1D, 2D and PDF417 barcodes printed on paper labels or displayed on the screen of a mobile phone. The Bluetooth® Low Energy 4.2 / classic V2.1 classic + EDR, Class 1 and NFC technology delivers the most efficient way to pair with smart phone and tablets (including iOS or android system) with just a touch. Moreover, the wireless technology keeps the scanner connected up to 100m from the computer, increasing productivity by allowing workers to move to the task. The MS652+ can be utilized with an auto mode that ensures no data is lost while it is out of range of the wireless signal, also upload the data to the back-end system automatically when it gets back in range, allowing users to complete their tasks without interruption.



EN Rev1.2 MS652+ Specifications

Functionality

Symbologies

1D: All major symbologies and PDF417

2D: QR Code, Data Matrix, Aztec Code, PDF417, Macro PDF417, Micro PDF417, MaxiCode, Coda block A, Codablock F, GS1 Composite, Han Xin Code, Australian Post, British Post, Canadian Post, InfoMail, Intelligent Mail Bar Code, Japanese Post, KIX (Netherlands) Post, GS1 Composite, Korea Post, Planet Code, Postal, Postnet

Operation Mode

Trigger mode, Presentation mode, Auto mode, Batch mode

Data Formatting

Prefix, Suffix, Code ID, Reformatting Date

Electrical

Operation Voltage

DC 5V +/- 10%

Current Consumption

Operation mode: 160mA, Standby mode: 23mA

Power off mode 1uA

RTC backup time

Support main battery replacement to keep RTC data within 5 mins.

Battery Type

Rechargeable Lithium-ion

Battery Capacity

800mAh / 3.7V

Charging Time

Fully charged in 4 hours

Operating Time

14 hours at 1 scan / 5 secs with good reading beep sound.

Charging Method

USB Cable or Battery Charging cradle

Environmental

ESD Protection

Functional after 8K Contact and 12K Air

Mechanical Shock

1.5M onto concrete (scanner only)

Operating Temperature

-10°C to 50°C

Storage Temperature

-20°C to 60°C

Relative Humidity

95% non-condensing

IP Rating

IP42

Accessories

Battery

Hand strap

Micro USB cable

Single slot cradle

4-Slot battery charger (optional)

5-Slot charging cradle

What comes in the box

MS652+ Scanner with trigger

module

Battery

USB charger cable

Wrist strap

Finger rubber pad

Two double sided tapes



Single slot cradle



4-Slot battery charger (optional)



5-Slot charging cradle

unitech Europe

Tilburg / Netherlands

<http://eu.ute.com> e-mail: info@eu.ute.com

unitech Japan

Tokyo

<http://jp.ute.com> e-mail: info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen

<http://cn.ute.com> info@cn.ute.com

Taipei <http://tw.ute.com> info@tw.ute.com

System

Connection

Connect to host with Windows, Android, or iOS

Memory

7.5Mbytes, store up to 590,000 of EAN13 codes

Keys

1 Scan Button

Optical & Performance

Scan Engine

Zebra SE2707

Sensor

CMOS sensor with 640 x 400 pixel

Light Source

1 Hyper Red 660nm LED

Ambient Light

Max 107, 639 lux (direct sunlight)

Skew Angle

60 degrees

Pitch Angle Sensor

60 degrees

Printing Contrast Scale

minimum 20%

Scan Speed

60 frame /sec

Depth of Field

(DOF PCS=80%)

SYMBOLGY / X-DIM TYPICAL RANGE*

Near

Far

5 mil Code 39 2.0 in / 5.1 cm 6.4 in / 16.2 cm

5 mil Code 128 2.5 in / 6.3 cm 5.0 in / 12.7 cm

6.6 mil PDF417 2.5 in / 6.3 cm 6.3 in / 16.0 cm

10 mil PDF417 1.8 in / 4.5 cm* 9.0 in / 22.8 cm

13 mil 100% UPC 2.0 in / 5.0 cm* 12.5 in / 31.7 cm

20 mil Code 39 2.0 in / 5.0 cm* 19.5 in / 49.5 cm

20 mil Data Matrix 1.5 in / 3.8 cm 13.5 in / 34.3 cm

20 mil QR Code 1.5 in / 3.8 cm 11.0 in / 27.9 cm

Communication

Radio

Bluetooth® Low Energy 4.2

Bluetooth® V2.1 + EDR, Class 1

Range

100M (line of sight)

Host Interface supported

USB

Protocol

HID / SPP (MS652+)

Mechanical

Scanner Dimension

50 x 71 x 21 mm

Scanner Weight

95g

Trigger Switch Life

1 million times

Regulatory Approvals

CE, FCC, BSMI, VCCI, TELEC, NCC



Headquarters

Taipei, Taiwan

<http://www.ute.com> e-mail: info@hq.ute.com

unitech America

Los Angeles

<http://us.ute.com> e-mail: info@us.ute.com

<http://can.ute.com> info@can.ute.com

Mexico

<http://latin.ute.com> e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East

Taipei

<http://apac.ute.com> info@apac.ute.com / info@india.ute.com

<http://mideast.ute.com> info@mideast.ute.com